



S-LBC857BLT1G

General Purpose Transistors PNP Silicon

1. FEATURES

- We declare that the material of product compliance with RoHS requirements and Halogen Free.
- S- prefix for automotive and other applications requiring unique site and control change requirements; AEC-Q101 qualified and PPAP capable.
- Moisture Sensitivity Level: 1
- ESD Rating – Human Body Model: >4000 V
– Machine Model: >400 V



2. DEVICE MARKING AND RESISTOR VALUES

Device	Marking	Shipping
S-LBC857BLT1G	3F	3000/Tape&Reel
S-LBC857BLT3G	3F	13000/Tape&Reel

3. MAXIMUM RATINGS(Ta = 25°C)

Parameter	Symbol	Limits	Unit
Collector-Emitter Voltage	VCEO	-45	V
Collector-Base Voltage	VCBO	-50	V
Emitter-Base Voltage	VEBO	-5	V
Continuous Collector Current	IC	-100	mA

4. THERMAL CHARACTERISTICS

Parameter	Symbol	Limits	Unit
Total Device Dissipation FR- 5 Board, (Note 1) TA = 25°C Derate above 25°C	PD	225 1.8	mW mW/°C
Thermal resistance from junction to ambient	RθJA	556	°C/W
Total Device Dissipation Alumina Substrate, (Note 2) TA = 25°C Derate above 25°C	PD	300 2.4	mW mW/°C
Thermal resistance from junction to ambient	RθJA	417	°C/W
Junction and Storage Temperature	TJ , Tstg	-55~+150	°C


1. FR-5 = 1.0 x 0.75 x 0.062 in.

2. Alumina = 0.4 x 0.3 x 0.024 in. 99.5% alumina.


5. ELECTRICAL CHARACTERISTICS (Ta= 25°C)

Characteristic	Symbol	Min.	Typ.	Max.	Unit
OFF CHARACTERISTICS					
Collector-Emitter Breakdown Voltage (IC = -10mA)	BVCEO	-45	-	-	V
Collector-Emitter Breakdown Voltage (IC = -10μA, VEB = 0)	BVCES	-50	-	-	
Collector-Base Breakdown Voltage (IC = -10μA)	BVCBO	-50	-	-	
Emitter-Base Breakdown Voltage (IE = -1μA)	BVEBO	-5	-	-	
Collector Cut-off Current (VCB = -30V) (VCB = -30 V, TA = 150°C)	ICBO	-	-	-15 -4	nA μA
ON CHARACTERISTICS					
DC Current Gain (IC = -2.0 mA, VCE = -5.0 V)	hFE	220	290	475	
Collector-Emitter saturation Voltage (IC = -10 mA, IB = -0.5 mA) (IC = -100 mA, IB = -5.0 mA)	VCE(sat)	-	-	-0.3 -0.65	V
Base-Emitter Saturation Voltage (IC = -10 mA, IB = -0.5 mA) (IC = -100 mA, IB = -5.0 mA)	VBE(sat)	-	-0.7 -0.9	-	V
Base-Emitter On Voltage (IC = -2.0 mA, VCE = -5.0 V) (IC = -10 mA, VCE = -5.0 V)	VBE(on)	-0.6 -	-	-0.75 -0.82	V
SMALL-SIGNAL CHARACTERISTICS					
Current-Gain — Bandwidth Product (IC = -10 mA, VCE = -5.0 V, f = 100 MHz)	fT	100	-	-	MHz
Output Capacitance (VCB = -10 V, f = 1.0 MHz)	Cob	-	-	4.5	pF
Noise Figure (IC = -0.2 mA, VCE = -5.0 V, RS = 2.0 kΩ f = 1.0 kHz, BW = 200 Hz)	NF	-	-	10	dB


6.ELECTRICAL CHARACTERISTICS CURVES




HFE vs. I_C



I_C vs. V_{CE}






V_{CE} vs. I_B





$V_{BE(on)}$ vs. I_C



6.ELECTRICAL CHARACTERISTICS CURVES(Con.)



7.OUTLINE AND DIMENSIONS



SECTION B-B




SOT23			
DIM	MIN	NOR	MAX
A	0.89	—	1.12
A1	0.01	—	0.10
A2	0.88	0.95	1.02
b	0.30	—	0.50
b1	0.30	0.40	0.45
c	0.08	—	0.20
c1	0.08	0.10	0.16
D	2.80	2.90	3.04
E	2.10	—	2.64
E1	1.20	1.30	1.40
e	0.95BSC		
e1	1.90BSC		
L	0.40	0.46	0.60
L1	0.54REF		
θ	0°	—	8°
All Dimensions in mm			

GENERAL NOTES

- 1.Top package surface finish Ra0.4±0.2um
- 2.Bottom package surface finish Ra0.7±0.2um
- 3.Side package surface finish Ra0.4±0.2um

8.SOLDERING FOOTPRINT



SOT-23	
DIM	(mm)
X	0.80
Y	0.90
A	2.00
B	0.95
C	0.95

DISCLAIMER

- Curve guarantee in the specification. The curve of test items with electric parameter is used as quality guarantee. The curve of test items without electric parameter is used as reference only.
- Before you use our Products for new Project, you are requested to carefully read this document and fully understand its contents. LRC shall not be in any way responsible or liable for failure, malfunction or accident arising from the use of any LRC's Products against warning, caution or note contained in this document.
- All information contained in this document is current as of the issuing date and subject to change without any prior notice. Before purchasing or using LRC's Products, please confirm the latest information with a LRC sales representative.